

History of Changes

[RSS](#)

1. Version 0.2 (2004/02/10)

- Implement stop/restart/graceful. All this requires is proper management of the callback process: call `apr_proc_fork()` with a process structure allocated in the (long-lived) process->pool of the main `server_rec`, then tell that pool to keep track of the subprocess using `apr_pool_note_subprocess`. Also, do the registration and callback child fork the second time the `post_config` hook is run. The first time appears to happen in some kind of bootstrap process which goes away, and forking the child from there orphans it. (ST)
- Only fork callback child if `APR_HAS_FORK` is defined. This is a conditional for the very existence of `apr_proc_fork()`, and I assume this isn't set on Win32 where we don't have to use the callback child anyway. (ST)
- Relicense under ASF 2.0 license. (ST)
- Port to Howl 0.9.2. (ST)
- Factored host registration code out of `post_config` hook handler so the code gets easier to read. (ST)
- Re-indented and reformatted closer to ASF code style. (ST)
- Add Forrest-based documentation (ST)

2. Version 0.1 (2003/11/24)

- Add Makefile stuff from `apxs -g`, with modifications to get actual `apxs` script from environment variable. (ST)
- Add README (ST)

3. Version Apachecon 2003 demo (unreleased)

- Initial import (ST)